



فرم تسمه 14M

کد فنی Part No.	تعداد دندانه Teeth No.	شکل Fig.	جنس Material	قطر روی تسمه ΦDp	قطر خارجی پولی ΦDe	قطر خارجی فلنج ΦDf	قطر نافی ΦDm	قطر پشت دندانه ΦDi	پهنای دندانه F	طول کل S	قطر سوراخ وسط Φd	فلنج flange
28-14M-55F	28	6F	STEEL (C45)	124.78	121.99	128	100	-	70	85	24	با فلنج With flanges
30-14M-55F	30	6F	STEEL (C45)	133.69	130.9	138	100	-	70	85	24	
32-14M-55F	32	6F	STEEL (C45)	142.6	139.81	154	100	-	70	85	24	
34-14M-55F	34	6F	STEEL (C45)	151.51	148.72	160	100	-	70	85	24	
36-14M-55F	36	6F	STEEL (C45)	160.43	157.64	168	100	-	70	85	24	
38-14M-55F	38	6F	STEEL (C45)	169.34	166.55	183	120	-	70	85	24	
40-14M-55F	40	6F	STEEL (C45)	178.25	175.46	188	120	-	70	85	24	
44-14M-55F	44	6F	STEEL (C45)	196.08	193.29	211	120	-	70	85	24	
48-14M-55F	48	10WF	CAST IRON	213.9	211.11	226	135	170	70	70	24	
56-14M-55F	56	10WF	CAST IRON	249.55	246.76	256	135	207	70	70	28	بدون فلنج Without flanges
64-14M-55F	64	10WF	CAST IRON	285.21	282.42	296	135	240	70	70	28	
72-14M-55	72	10A	CAST IRON	320.86	318.07	-	135	280	70	70	28	
80-14M-55	80	10A	CAST IRON	356.51	353.72	-	135	314	70	70	28	
90-14M-55	90	10A	CAST IRON	401.07	398.28	-	135	358	70	70	28	